

MATERIAL SAFETY DATA SHEET

DISTRIBUTED BY: WALLACE CONSTRUCTION SPECIALTIES LTD.
825 MacKay St.
Regina, SK S4N 2S3

EMERGENCY/INFORMATION. PHONE: 522-2811 OR CANUTEC (613) 996-6666

SECTION 1: PRODUCT IDENTIFICATION

PRODUCT NAME: ACRYLBOND PRODUCT NUMBER: 3301AC

WHMIS CLASSIFICATION: D2b.
HMIS. RATING: HEALTH: 1 FLAMMABILITY: 0
REACTIVITY: 0 PERSONAL PROTECTION: B

SECTION 2: HAZARDOUS INGREDIENTS

Ingredient: CAS Number % Weight TLV.
AMMONIA 7664-41-7 0.5-1.5 25-50 ppm

SECTION 3: PHYSICAL DATA

PHYSICAL DESCRIPTION: Thick, white odourless liquid.
EVAPORATION RATE: As water.
VAPOUR DENSITY: As Water.
BOILING POINT: 100° C
FREEZING POINT: 0° C
SPECIFIC GRAVITY: 1.0
pH: 9.0

SECTION 4: FIRE AND EXPLOSION DATA

FLAMMABILITY CLASSIFICATION: Not flammable.
EXPLOSIVE LIMITS: None.
FLASH POINT & METHOD: Over 100 Deg. C (TCC).
EXTINGUISHING MEDIA: Foam, CO2, dry chemical, water.
UNUSUAL FIRE AND EXPLOSIVE HAZARDS: None.

SPECIAL FIRE-FIGHTING PROCEDURES:
Use water spray to cool containers, to prevent pressure build up.

SECTION 5: HEALTH HAZARD DATA

EFFECTS OF OVER EXPOSURE:
SKIN: May cause irritation.
EYES: Eye contact may cause irritation.
INHALATION: Not normally a hazard.
INGESTION: The health effects of this product have not been tested although it is not believed to be hazardous based on its composition.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: None known.

EMERGENCY AND FIRST AID

PROCEDURES:

PRIMARY ROUTE(S) OF ENTRY: Skin & eye contact.

SKIN AND EYES: Flush well with plenty of running water for at least 5 minutes.

If irritation develops contact a physician.

INHALATION: Remove person away from exposure & consult a physician.

Inhalation exposure is not normally a hazard.

INGESTION: Consult physician.

Although the concentration in this product is low, the high vapour pressure of ammonia makes it possible to exceed the TLV or PEL in drumhead spaces or other confined areas. The liberation of ammonia may be retarded by chemical neutralisation in the product.

No constituents are listed as carcinogens by NTP, IRAC or OSHA

SECTION 6: REACTIVITY DATA.

MATERIAL STABILITY: Stable.

HAZARDOUS POLYMERIZATION: None.

HAZARDOUS DECOMPOSITION PRODUCTS:

Normal combustion products include oxides of Carbon & Nitrogen.

CONDITIONS TO AVOID: None known.

MATERIALS TO AVOID: Strong oxidizers.

SECTION 7: SPILL OR LEAK PROCEDURES.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Dilute with water & pick up with an inert absorbent.

WASTE DISPOSAL METHOD:

Dispose of only in accordance with all Government regulations.

This product is not considered to be a hazardous waste.

RESPIRATORY PROTECTION: Not normally required.

VENTILATION: Normal ventilation.

PROTECTIVE GLOVES: Waterproof gloves are recommended.

OTHER PROTECTIVE EQUIPMENT: No special requirements.

SECTION 8: SPECIAL PRECAUTIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

- Avoid opening drums in unventilated areas (ammonia vapours).
- Do not take internally. Avoid eye contact.
- Avoid prolonged or repeated contact with skin.

SECTION 9: SHIPPING AND LABEL INFORMATION.

DOT SHIPPING DATA: Not regulated.

SECTION 10: PREPARATION DATA.

PREPARED BY: WALLACE CONSTRUCTION SPECIALTIES LTD.
DATE: 16 NOVEMBER 2012

The information contained herein is based on data believed to be reliable by WALLACE CONSTRUCTION SPECIALTIES LTD. It is true and accurate to the best of our knowledge, but is not intended to be all-inclusive. Users should consider this information as a supplement to other information gathered by them and must make their own determination of suitability and completeness to assure proper safe use and disposal of these materials.