

Acousti-Mat® LP

Acousti-Mat® LP warms up Ireland
Therma-Floor® over Acousti-Mat® LP over heating cables.

[Project Spotlight Library](#)



Maxxon®	Gypsum Underlayments	Self-Leveling Floors	Sound Control	Moisture Vapor Treatments
---------	----------------------	----------------------	---------------	---------------------------

- Data Sheet
- Specifications
- Fire Ratings/Detail Drawings
- Finished Floor Support
- Downloads

Self-Leveling Floors > Level-Right® WearTop > Data

Level-Right® WearTop Data Sheet



Manufacturer:

Maxxon® Corporation
 920 Hamel Road
 P.O. Box 253
 Hamel, MN 55340
 Phone: 1-800-356-7887 or (763) 478-9600
 Fax: (763) 478-2431

Product Description:

Ideal for fast-track retrofits, **Level-Right® WearTop** is the answer for old or damaged concrete floors that need a new, smooth, and level wear surface. It installs with minimal prep and fast drying ti

portland cement-based topping, **Level-Right® WearTop** is pumped in and quickly fills dips, voids, and cracks to create a flat, hard wear surface. Get the look and strength of new construction, with less time and lower cost with the top solution for resurfacing concrete floors.



Product Advantages:

- High strength
- High fluidity for fast installation
- Remains workable for over 10 minutes with slight agitation
- Pourable or pumpable
- Low in-place cost
- Non-shrinking
- Ready for foot traffic in two hours
- Return to service in 24 hours
- Highly durable to resist gouging from construction activity

Technical Data:

Installation Depth:	0" - 1½" (38 mm)
Packaging:	50 lb. Bag (22.7 kg)
Working time:	10 minutes @ 70 °F (21°C)
Final Set:	60-90 minutes @ 70 °F (21°C)
Color:	Gray or white
Compressive strength (modified ASTM C109)	4000 psi (27 MPa) (3 day) 5000 psi (34 MPa) (7 day) 6200 psi (43 MPa) (28 day)
Dry Density:	120 lb/ft³ (1920 kg/m³)
Tensile strength (ASTM C348)	720 psi (5 MPa) (28 day)
Flexural strength (ASTM C190)	1440 psi (10 MPa) (28 day)

'Green' Information:

Sample USGBC LEED Credit Areas*			
Project	Credit	Category	How Requirement is Fulfilled
Materials & Resources	MR 2	Construction Waste Management	Recyclable packaging and shipping materials
	MR 5	Local/Regional Materials	Manufactured in West Grove, PA 19390; Job site manufactured with local sand & water

* Credits may vary depending on project type and Maxxon products used.

For additional information on the USGBC and Level-Right WearTop's qualifications for earning LEED

see our "[Green](#)" page.

Maxxon provides underlayment, Gyp-Crete, gypsum concrete and other flooring underlayment products for new construction, remodeling and renovation.
This site and all contents copyright © 2001-2011 MAXXON Inc. All rights reserved.

[Home](#) | [Canada](#) | [Ireland](#) | [en français](#) | [en español](#)