



ALLIED

Silt Fence

Silt Fence is a woven fabric that temporarily controls sediment. Ideally used on construction sites to protect water quality in nearby streams, rivers and lakes from sediment in storm water runoff.

Fabric Property	Test Method	Units	Min. Average Roll Value
Grab Tensile	ASTM D 4632	lbs.	65
Elongation	ASTM D 4632	lbs.	18
Trap Tear Strength	ASTM D 4533	lbs.	55
Puncture Resistance	ASTM D 4833	lbs.	40
Mullen Burst	ASTM D 3786	Psi	160
Permittivity	ASTM D 4491	Sec-1	.1
Water Flow	ASTM D 4491	gpm/ft ²	10
UV Resistance	ASTM D 4355	% Strength Retained	80
AOS	ASTM D 4751	US Sieve	40

Values Provided represent expected values at time of manufacture. This document provides the characteristic properties of the product described.

Roll Dimensions – 3’x100’ with 1.25”x1.25”x42” wooden stakes

Seller’s and manufacturer’s only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use or the inability to use the product. Before using, user shall determine the suitability of the product for his/her intended use, and user assumes all risk and liability whatsoever in connection therewith.