



DRAWINGS FOR ILLUSTRATIVE PURPOSES ONLY

BL-607

The BL-607 is a wire tie and plate combination system which provides adjustability, minimal free-play, strength, stiffness, positive connection, corrosion-resistance, and is test rated. The anchor plate has been designed for mounting on the surface of the stud.

Dimensions:

Base Plate: 16 gauge (1.5 mm) thick x 2" (50 mm) wide
Length to accommodate various insulation thicknesses.

Base Plate Material:

16 gauge Carbon Steel ASTM A366, Hot-Dip Galvanized per ASTM A153, C1 B2

16 gauge Stainless Steel per ASTM 167

Flex-O-Lok Tie Material:

3/16" (4.76 mm) Diameter Wire

Carbon Steel per ASTM A 82, Hot-Dip Galvanized per ASTM A153, C1 B2

Stainless Steel per ASTM A580

Blok-Lok manufactures steel wire products from a minimum of 95% post-consumer recycled material.

Finish:

- Hot-Dip Galvanized per ASTM A153, C1 B2
 Stainless Steel Type 304 per ASTM 167

Note: Blok-Lok recommends Stainless Steel for maximum protection against corrosion.

Fastener:

- 1 1/2" Self-Drilling, Self-Tapping / without Sealant Washer
 2" Self-Drilling, Self-Tapping / with Sealant Washer

Insulation Thickness:

- 0" 1" 1 1/2" 2"
 2 1/2" 3" 3 1/2" 4"

Flex-O-Lok® Tie:

- BLT-9 BLT-9 Seismic

Tie Length:

- 3" 4" 5"
 6" 7"