

GRIDMATE[®] BR

PLASTIC INSULATION FASTENERS

FOR FASTENING INSULATION TO CONCRETE.




Applications

- All Polymer Modified (PM) Systems.
- Modified Stucco Systems.
- Expanded lath over EPS, XPS or ISO rigid insulation.
- Fiberglass fabric over rigid insulation.
- Wire mesh over rigid insulation.
- Attaching rigid insulation to masonry or concrete.

Product Features

- Textured head allows for coverage of stucco
- Non cold-conductive
- Made from strong Polypropylene
- Textured head allows for coverage of stucco
- Fins provide high holding power
- Non Corrosive

Selector Guide and List Price



Key #	Cat #	Description	Hole Dia.	Grip Range	Box Qty	Case	
						Qty.	Wt.
56040	56040	2-3/4" BR Anchor	5/16"	1 1/2"	N/A	250	2
56050	56050	3-1/2" BR Anchor	5/16"	2 1/2"	N/A	200	2.5
56060	56060	4-3/8" BR Anchor	5/16"	3 1/4"	N/A	200	3
56070	56070	5-1/4" BR Anchor	5/16"	4"	N/A	100	2

Technical Data

Base Material	Embedment	Ultimate Pullout
25 MPA Concrete	1 1/8"	113 lbs.
Concrete Block	1 1/8"	103 lbs.
Brick	1 1/8"	103 lbs.
8 fasteners per 4' x 8' sheet required		