



357SA

S P R A Y A D H E S I V E

NASHUA® 357SA

Spray Adhesive - Low VOC

APPLICATIONS

- Ideal for bonding carpets.
- Ideal for securing labels.
- Bonds fabric, fiberglass insulation, plastic films, felt, rubber, leather, cork, paper, cardboard, urethane foam, foil to metal, wood to themselves and a variety of other substrates.
- Bonds PE to concrete block, wood, and other hard-to-bond surfaces.



PRODUCT DESCRIPTION

- Contains no methylene chloride.
- Application temp: -10° to 180°F
- Lace spray pattern.
- Net wt. 17oz; 23.8 fluid oz.
- Bonding time 15 sec. - several hours
- Solvent odor.
- Color: Water white.
- Shelf-life: One year from the date of manufacture.
- Extremely flammable.
- VOC Content <55%.

FEATURES & BENEFITS

- Fast skin, fast grab, low soak-in adhesive.
- Useful for both permanent and temporary bonds.
- Good UV, moisture, and oxidation resistance.
- Meets requirements of SCAQMD Rule 1168 and GreenSeal GS-36 for VOC content.

Application Instructions

- Shake well before applying. Spray an even coat from a distance of 6-8 inches.
- For permanent bonds, spray both surfaces. Allow 1-2 minutes for tack to develop. Then bond with firm pressure.
- For temporary bonds, apply a light, even coat to one surface; allow tack to develop. Then bond with firm pressure.
- When finished spraying, turn can upside down and spray for 2 seconds to prevent nozzle from clogging.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.



25 Forge Pkwy Franklin, MA 02038
1-800-343-7875 Fax 1-800-328-4822
www.berryplastics.com

Nieuwlandlaan B15 Aarschot Belgium
Ph: +32(0)16/55 36 00 Fax: +32 (0)16/55 36 74
1/12/2010