



30 Commerce Road
Rockland, MA 02370

Phone: 1-800-343-1076
Fax: 781-871-0065

Technical Data Sheet

1551CW

WMP[®]-50 POLYPROPYLENE FACING TAPE

DESCRIPTION: A tri-directionally reinforced, UL listed, white polypropylene/ scrim/metallized polyester facing tape coated with a specialty acrylic pressure sensitive adhesive system. Combining superior quick stick at normal temperatures with superior low temperature performance down to 10°F, this is the ultimate in cold weather tapes. Recommended for use at elevated temperatures also.

APPLICATIONS: Primarily used as a closure system and vapor seal on Lamtec WMP[®]-50 faced thermal insulation.

TECHNICAL DATA

	<u>IMPERIAL</u>	<u>METRIC</u>
Substrate Thickness:	10 mils (0.010")	0.2540 mm
Adhesive thickness:	1.85 mils (0.00185")	0.0470 mm
Adhesion (PSTC 101):	75 oz/inch width	21.2 N/2.5 cm
Tensile (PSTC 131):	65 lbs/inch width	294 N/2.5 cm
Minimum Application Temperature:	15°F	-9.4°C
Maximum Use Temperature:	240°F	116°C
Release liner:	43 lbs/ream Polycoated natural kraft	70 GSM

IMPORTANT INFORMATION:

The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using the product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.