



# MATERIAL SAFETY DATA SHEET LEVEL-RIGHT PLUS, FS-10 AND FEATHEREDGE

MSDS No. 100B  
Page 1 of 3

Maxxon® Corporation  
920 Hamel Road, PO Box 253  
Hamel, MN 55340

Issue date: January, 2006  
Revision date: December , 2010

## SECTION I PRODUCT IDENTIFICATION

Product Name: Level-Right® Plus  
Level-Right® FS-10  
Level-Right® Featheredge  
Product Number: 43A-14256  
Product Use: Floor Underlayment  
Chemical Emergency or information, call: Maxxon Corporation, 763-478-9600 (Q.A. Dept.)  
or Chem-Trec at 1-800-424-9300

## SECTION II HAZARDOUS INGREDIENTS

Hazardous components (Specific chemical identity: <u>common name(s)</u> )	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>Other Limits Recommended</u>
Sodium Naphthalene Sulfonate	N/A	N/A	
Glassy Calcium Silicates			
	3Ca O SiO <sub>2</sub>		
	2Ca O SiO <sub>3</sub>		
	3Ca O Al <sub>2</sub> O <sub>3</sub>		
	S		
Free silica	SiO <sub>2</sub>		
Alloys	Al <sub>2</sub> O <sub>3</sub>		
Metallic coating	Fe <sub>2</sub> O <sub>3</sub>		

## SECTION III PHYSICAL DATA

BOILING POINT: N/A  
VAPOR PRESSURE: N/A  
VAPOR DENSITY: N/A  
SPECIFIC GRAVITY (H<sub>2</sub>O): 2.5



# MATERIAL SAFETY DATA SHEET

## LEVEL-RIGHT PLUS, FS-10 AND FEATHEREDGE

MSDS No. 100B  
Page 2 of 3

MELTING POINT:	N/A
EVAPORATION RATE:	N/A
SOLUBILITY IN WATER:	(.08 - .09) %
APPEARANCE AND ODOR:	grey, odorless

### SECTION IV FIRE AND EXPLOSION DATA

FLASH POINT:	N/A
FLAMMABLE LIMITS:	N/A
HAZARDOUS COMBUSTION PRODUCTS:	None
AUTOIGNITION TEMPERATURE:	N/A
FIRE EXTINGUISHING MEDIA:	N/A

### SECTION V REACTIVITY DATA

STABILITY:	Stable
INCOMPATIBILITY (MATERIALS TO AVOID):	None
CONDITIONS TO AVOID:	None
HAZARDOUS DECOMPOSITION PRODUCTS:	None
HAZARDOUS POLYMERIZATION:	Will not occur

### SECTION VI HEALTH HAZARD DATA

Inhalation of respirable crystalline silica dust over a long period of time has shown to cause pneumoconiosis (silicosis).

Signs and Symptoms of Exposure: Wet material can dry skin and cause alkali burns. Dust can irritate eyes and upper respiratory tract if inhaled. Ingestion may result in obstruction, get medical attention.



## MATERIAL SAFETY DATA SHEET LEVEL-RIGHT PLUS, FS-10 AND FEATHEREDGE

MSDS No. 100B  
Page 3 of 3

### SECTION VII EXPOSURE CONTROL/PERSON PROTECTION

**Engineering Controls:** Provide local exhaust as necessary to meet OSHA requirements for dust exposure. Use wet methods, if appropriate, to reduce generation of dust.

**Skin Protection:** Protective gloves may be desirable to prevent drying or irritation of hands.

**Respiratory Protection:** Wear NIOSH/OSHA approved respirator when permissible exposure limits to dust may be exceeded.

**Eye Protection:** Recommend eye goggles or safety glasses for nuisance dust.

### SECTION VIII HANDLING AND STORAGE

**SPILLAGE:** Use dry clean up method that does not disperse dust into the air. Do not breathe dust, avoid contact with eyes.

**WASTE DISPOSAL:** Material can be disposed of as common waste.

**HANDLING AND STORAGE:** Keep material dry. High humidity or moisture may cause premature hardening of material.