

Spotlight on Dura-Cap®

Market Common with 34,000 sq. ft. of Dura-Cap® topping corrugated steel deck.

[Project Spotlight Library](#)



Maxxon®

Gypsum Underlayments

Self-Leveling Floors

Sound Control

Moisture Vapor Treatments

Data Sheet

Downloads

Self-Leveling Floors > Level-Right® FeatherEdge> Data

Level-Right® FeatherEdge Data Sheet

LEVEL-RIGHT®
FeatherEdge

Manufacturer:

Maxxon® Corporation
920 Hamel Road
P.O. Box 253
Hamel, MN 55340
Phone: 1-800-356-7887 or (763) 478-9600
Fax: (763) 478-2431

Product Description:

Level-Right® FeatherEdge is a specially formulated, fast setting, polymer-modified portland cement based patching compound. Mixed with water, it is used for patching over all gypsum underlayments, wood and concrete subfloors. It can be used as an embossing leveler over vinyl, VCT, cement, terrazzo and old adhesives.



Product Advantages:

- Portland cement-based, will not stain or mildew
- Exceptional bond to gypsum underlayments, wood and concrete
- No sand, allowing for featheredge
- Meets ASTM F-710 Preparing Concrete to Receive Resilient Flooring
- Latex modified
- Fast drying, most floor goods installed in as little as 2 - 4 hours
- Non-shrinking

Technical Data:

Packaging	25 lb. Bag (11.3 kg)
Working time	5 to 10 minutes
Final Set	30 minutes
Compressive Strength	5500 psi (38 Mpa) 28 days (modified ASTM C109)
Color	Gray
Thickness	Coverage (Approximate)
1/32" (0.8 mm)	100-140 sq. ft. (9.3-12 m²)
1/16" (1.5 mm)	50-70 sq. ft. (4.6-6.5 m²)
1/8" (3.1 mm)	25-35 sq. ft. (2.3 -3.3 m²)

Maxxon provides underlayment, Gyp-Crete, gypsum concrete and other flooring underlayment products for new construction, remodeling and renovation.

This site and all contents copyright © 2001-2011 MAXXON Inc. All rights reserved.

[Home](#) | [Canada](#) | [Ireland](#) | [en français](#) | [en español](#)