

B-11 Flat Washers

Dayton Superior B-11 Flat Washers are made from flat steel plate and are available in the sizes shown in the accompanying chart. For best results the space spanned by the washer should not exceed the bolt diameter plus 1/4".



-11 Flat Washer	at Washer
-----------------	-----------

To Order: Specify: (1) quantity, (2) name, (3) bolt
Example:

1,200 pcs. B-11 Standard, 1/2" bolt.

B-11 Flat Washer Selection Chart				
Bolt Diameter	Туре	Safe Working Load (Ibs.)	Size	
1/2"	Standard	6,750	3" x 4" x 1/4"	
1/2"	Heavy	8,750	4" x 5" x 1/4"	
3/4"	Standard	14,000	4" x 5" x 3/8"	
3/4"	Heavy	14,000	5" x 5" x 3/8"	
1"	Standard	18,500	5" x 5" x 1/2"	
1"	Heavy	38,000	7" x 7" x 3/4"	
1 1/4"	Standard	22,750	5" x 5" x 5/8"	
1 1/4"	Heavy	50,750	7" x 7" x 3/4"	
1 1/2"	Standard	26,250	5" x 5" x 3/4"	
1 1/2"	Heavy	41,500	7" x 7" x 3/4"	

SWL provides a factor of safety of approximately 2 to 1

B-12 Coil Rod


Dayton Superior B-12 Coil Rod is available in 1/2" to


diameter.

B-12 Coil Rod

1-1/2" diameters in 12' lengths. Field cutting can be accomplished with bolt cutters or carborundum blades.

B-12 threaded rod can be used with Coil Ties in many forming combinations to tie formwork, for adjustable ties, for concrete embedments and/or emergency ties.





To Order:

Specify: (1) quantity, (2) name, (3) diameter, (4) length.

Example:

500 pcs. B-12 Coil Rod, 1" diameter x 12'-0" long.

B-12 Coil Rod Selection Chart Safe Working Loads Minimum Tensile Yield Minimum Coil Rod **Root Area** Stress Stress Coil Tension Shear Diameter Penetration (lbs.) (lbs.) (sq. in.) (psi.) (psi.) 2" 1/2" 9,000 6,000 .1385 130,000 110,000 5/8" 12,000 8,000 .2124 113,000 96,000 2-1/4" 3/4" 18,000 12,000 .3079 117,000 100,000 2-1/4" 7/8" 24,000 16,000 .4477 117,000 100,000 2-1/2" 1" 38,000 25,300 .5410 140,000 120,000 2-1/2" 1-1/8" 45,000 30,000 .7163 126,600 105,000 2-1/2" 1-1/4" 56,000 37,500 .9161 123,000 105,000 2-1/2" 68,000 45,300 1.3892 98,000 85,000 3" 1-1/2"

SWL provides a factor of safety of approximately 2 to 1. Warning: See Page 7 before using B-12 Coil Rod.