



CALL US TOLL FREE: (800) 875-7768



Color Chart

Actual PVC colors may vary slightly from printed colors shown.

SIZING CHART FOR PVC FITTING COVERS

BASED ON O.D. PIPE INSULATION CONFORMING TO ASTM STD C-585-76

COMBINATION SHORT & LONG RADIUS FITTING COVERS IN COMPLIANCE WITH ASTM STANDARDS

Iron Pipe Size	Insulation Thickness											
	1/2"	OCF	1"	1 1/2"	2"	2 1/2"	3"	3 1/2"	4"	5"	5 1/2"	6"
3/8"	#2		#7	#9						WHERE # FITTINGS ARE NOT SHOWN ON THESE CHARTS, GO TO CHART IN THE MAIN CATALOG AND SELECT # FITTING FROM MAX O.D.		
1/2"	3		7	10	#12	#15	#17	#18	#19			
3/4"	4	#5	7	10	12	15	17	18	19			
1"	5		9	11	13	15	17	18	19			
1 1/4"	6	7	9	12	13	15	17	18	19			
1 1/2"	7		10	12	15	17	18	19	20			
2"	9		11	13	15	17	18	19	20	#22	#23	#23
2 1/2"	10		12	15	17	18	19	20	21	22	23	24
3"	11		13	15	17	18	19	20	21	23	24	25
3 1/2"	12		15	17	18	19	20	21	22	23	24	25
4"	13		15	17	18	19	20	21	22	24	25	26
5"	15		17	18	19	20	21	22	23	25	26	27

Iron Pipe Size	Insulation Thickness											
	1/2"	OCF	1"	1 1/2"	2"	2 1/2"	3"	3 1/2"	4"	5"	5 1/2"	6"
6"	17		18	19	20	21	22	23	24	26	27	28
8"	19		20	21	22	23	24	25	26	28	29	30
10"			22	23	24	25	26	27	28	30	31	32
12"			24	25	26	27	28	29	30	32	34	34
14"			25	26	27	28	29	30	31	33	34	35
16"			27	28	29	30	31	32	33	35	36	37
18"			29	30	31	32	33	34	35	37	38	39
20"			31	32	33	34	35	36	37	39	40	41
22"			33	34	35	36	37	38	39	41	42	43
24"			35	36	37	38	39	40	41	43	44	45

The above are combination sizes that fit short and long radius screwed and welded elbows, long radius weld ells, and screwed and welded tees. Fitting sizes below the dark line will not fit most long radius 90 degree Elbows properly; order fitting covers for these long radius 90 degree sizes by specific pipe size and insulation thickness. The above combination sizes will fit all 45 degree elbows. To find exact number fitting required for your max O.D., go to chart in the main catalog and choose fitting number in column next to Max Fitting O.D. column.

Copper Tubing Size	Insulation Thickness												
	ACTUAL O.D.	1/2"	OCF	1"	1 1/2"	2"	2 1/2"	3"	3 1/2"	4"	5"	5 1/2"	6"
3/8"	1/2"			#5	#9	#11	#13	#15					
1/2"	5/8"	#2	#3	7	9	11	13	15					
3/4"	7/8"	3	3	7	10	12	15	17	#18	#19			
1"	1 1/28"	4	5	7	10	12	15	17	18	19			
1 1/4"	1 3/8"	5	5	9	11	13	15	17	18	19			
1 1/2"	1 5/8"	6	7	9	12	13	15	17	18	19			
2"	2 1/8"	8	9	10	12	15	17	18	19	20	#22	#23	#23
2 1/2"	2 5/8"	9	10	11	13	15	17	18	19	20	22	23	24
3"	3 1/8"	10	11	12	15	17	18	19	20	21	23	24	25
3 1/2"	3 5/8"	11	11	13	15	17	18	19	20	21	23	24	25
4"	4 1/8"	12	13	15	17	18	19	20	21	22	24	25	26
5"	5 1/8"	14	15	17	18	19	20	21	22	23	25	26	27
6"	6 1/8"	16	17	18	19	20	21	22	23	24	26	27	28

O.D. Sizing Chart

Fits O.D. MAX.	ONE PIECE PVC COVER SIZE
1 5/8"	#2
1 7/8"	#3
2 1/8"	#4
2 3/8"	#5
2 5/8"	#6
2 7/8"	#7
3 1/8"	#8
3 1/2"	#9
4"	#10
4 1/2"	#11
5"	#12
5 9/16"	#13
6 1/8"	#14
6 5/8"	#15
7 1/8"	#16
7 5/8"	#17
8 5/8"	#18
9 5/8"	#19
10 3/4"	#20
11 3/4"	#21

Fits O.D. MAX.	ONE PIECE PVC COVER SIZE
12 3/4"	#22
14"	#23
15"	#24
16"	#25
17"	#26
18"	#27
19"	#28
20"	#29
21"	#30
22"	#31
23"	#32
24"	#33
25"	#34
26"	#35
27"	#36
28"	#37
29"	#38
30"	#39
31"	#40
32"	#41



Eastern States Insulation Contractors Association, Inc.



Member Of
Midwest Insulation Contractors Association



PROTO CORPORATION EMPLOYS
BEST ENVIRONMENTAL PRACTICES
FOR A GREENER TOMORROW.