


# DOOR THRESHOLDS

Abrasive cast metal

Cast abrasive-surfaced door thresholds provide safe footing at entrances for the life of a building. The designs shown here are the most popular. They can be factory notched to fit door jambs, eliminating costly field labor. Thresholds are ready for immediate installation, with holes factory drilled and countersunk.

## How To Specify

All thresholds shall be cast abrasive style No. \_\_\_\_\_ as manufactured by American Safety Tread Company, Helena, Alabama 35080, Telephone 1-800-245-4881. Thresholds shall be cast in Alumacast, Feracast, Bronzecast or Nickelcast with #24 virgin grain Silicon Carbide granulees embedded into the walking surface while the matrix is in a molten state. All metals shall be furnished in natural metal finish. Feracast shall have one coat of shop applied black paint.



**STYLE 810**  
Standard height 3/8"  
Width to order up to 18"



**STYLE 814**  
Standard height 3/8"  
Standard widths 4" 5" 6"



**STYLE 811**  
Standard height 1/2"  
Standard widths 4" 5" 6"



**STYLE 815**  
Standard height 1/2"  
Standard widths 4" 5" 6"



**STYLE 812**  
Height under door 5/8"  
Door stop height 1/2"  
Standard widths 4" 5" 6"



**STYLE 815M**  
Standard height 1/2"  
Standard widths 4" 5" 6"



**STYLE 813**  
Height under door 3/4"  
Standard height 3/8"  
Standard widths 4" 5" 6"



**STYLE 815S**  
Height under door 1/2"  
Standard height 3/8"  
Standard widths 4" 5" 6"

### HOME

### CAST STAIR NOSINGS

### EXTRUDED STAIR NOSINGS

### STRUCTURAL STAIR TREADS

### RENOVATION TREADS

### DOOR THRESHOLDS

### GRATING NOSINGS & ELEVATOR DOOR SILLS

### CUT SHEETS

### CONTACT US